

# Safety Data Sheet

**RCC Corrosion Control / SDS #: RCC-20381 / Revision Date: 09/01/2022**

---

## **1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT NAME: COROGROUT VE RESIN

CHEMICAL FAMILY: Vinyl Ester in Styrene solvent

PRODUCT USE: Coating material

MANUFACTURER: RCC Corrosion Control  
1450 Hoff Industrial Drive  
O'Fallon, MO 63366  
Phone: 636-697-4659

24-Hour Emergency Phone Number: North America: 800-424-9300 (CHEMTREC)  
International: 703-527-3887 (CHEMTREC) Collect Calls Accepted

## **2. HAZARD IDENTIFICATION**

### **GHS-Classification**

Flammable Liquids, Category 3  
Acute Toxicity, Category 4, Inhalation  
Eye irritation, Category 2A  
Skin irritation, Category 2  
Germ cell mutagenicity, Category 2  
Carcinogenicity, Category 2  
Reproductive toxicity, Category 2  
Specific target organ systemic toxicity – single exposure, Category 1, Central Nervous System  
Specific target organ systemic toxicity, single exposure, Category 3  
Specific target organ systemic toxicity, repeated exposure, Category 1, Blood, Liver, Nervous system, Respiratory tract/organ  
Aspiration Hazard, Category 1  
Acute aquatic toxicity, Category 2

### **GHS-Labeling**

#### **Pictogram(s):**



**Signal Word:** Danger

### **Hazard Statements**

# Safety Data Sheet



**RCC Corrosion Control / SDS #: RCC-20381 / Revision Date: 09/01/2022**

---

H226: Flammable liquid and vapor  
H315: Causes skin irritation  
H319: Causes serious eye irritation  
H332: Harmful if inhaled  
H335: May cause respiratory irritation  
H336: May cause drowsiness or dizziness  
H361: Suspected of damaging fertility or the unborn child.  
H351: Suspected of causing cancer  
H372: Causes damage to organs (Blood, Liver, Nervous system, Respiratory tract/organ) through prolonged or repeated exposure  
H401: Toxic to aquatic life

## **Precautionary Statements**

### Prevention:

P201: Obtain special instructions before use  
P202: Do not handle until all safety precautions have been read and understood  
P210: Keep away from heat/sparks/open flames/hot surfaces. – No Smoking  
P233: Keep container tightly closed  
P240: Ground/bond container and receiving equipment  
P241: Use explosion-proof electrical/ventilating/lighting/equipment  
P242: Use only non-sparking tools  
P243: Take precautionary measures against static discharge  
P260: Do not breathe dust/fume/gas mist/vapor/spray  
P264: Wash skin thoroughly after handling  
P270: Do not eat, drink or smoke when using this product  
P271: Use only outdoors or in a well-ventilated area  
P273: Avoid release to the environment  
P280: Wear protective gloves/protective clothing/eye protection/face protection

### Response:

P301+ P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
P303 + P361 + P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304 + P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P307 + P311: IF exposed: Call a POISON CENTER or doctor/physician.

P321: Specific treatment (see supplemental first aid instructions on this label)  
P331: D NOT induce vomiting  
P332 + P313: If skin irritation occurs: Get medical advice/attention  
P337 + P313: If eye irritation persists: Get medical advice/attention  
P362: Take off contaminated clothing and wash before reuse  
P370 + P378: In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction

### Storage:

P403 + P233: Store in a well-ventilated place. Keep container tightly closed

# Safety Data Sheet



RCC Corrosion Control / SDS #: RCC-20381 / Revision Date: 09/01/2022

---

P405: Store locked up

Disposal:

P501: Dispose of contents/container to an approved waste disposal plant.

### 3. COMPOSITION/ INFORMATION ON INGREDIENTS

**Chemical characterization** (Mixture)

Epoxide-vinyl ester-resin in styrene

Component	CAS#	% By Wt.
Styrene	100-42-5	40 - 50

### 4. FIRST AID MEASURES:

#### **General Information**

Move affected person(s) from danger area. Remove contaminated/soaked clothing immediately. In the event of persistent symptoms, seek medical attention. Do not leave the victim unattended. Symptoms of poisoning may only appear several hours later. Show this Safety Data Sheet to the doctor in attendance.

**If inhaled:** Remove to fresh air. If breathing is difficult administer oxygen. Get immediate medical help.

**In case of skin contact:** If on skin, rinse well with water. Remove contaminated clothing. Consult a doctor if irritation persists.

**In case of eye contact:** Immediately flush eye(s) with plenty of water. Remove contact lenses. Hold eyes open and flush with water, including under eyelids, for at least 15 minutes. If irritation persists, seek medical attention.

**If swallowed:** Keep respiratory tract clear. Induce vomiting only upon the advice of a physician. Do not give milk. Immediately give plenty of water, if possible charcoal slurry. BEWARE, danger of aspiration! Never give anything by mouth to an unconscious person. Get immediate medical help.

# Safety Data Sheet



RCC Corrosion Control / SDS #: RCC-20381 / Revision Date: 09/01/2022

---

## 5. FIRE FIGHTING MEASURES

**Suitable extinguishing media:** Alcohol-resistant foam, carbon dioxide, dry chemical, water spray.

**Unsuitable extinguishing media:** High volume water jet.

**Specific hazards during fire fighting:** Do not allow run-off from fire fighting to enter drains or water courses.

**Special protective equipment for fire-fighters:** Wear self-contained breathing apparatus and protective suit.

**Special exposure hazards arising from combustion:** Carbon dioxide and carbon monoxide. Irritant/corrosive, flammable, as well as toxic fumes.

**Additional information:** Vapors are heavier than air and spread along the ground. Vapor/air mixture can be explosive, even in empty containers. Cool containers at risk with water spray. Collect contaminated firefighting water separately. Do not allow to enter drains or water courses. Fire residues and contaminated firefighting water should be disposed of in accordance with local, state, and federal regulations.

## 6. ACCIDENTAL RELEASE MEASURES:

**Personal precautions:** In case of vapor formation, use respirator to avoid breathing fumes. Ensure adequate ventilation. Remove any affected persons to safety. Use PPE. Keep all sources of ignition away!

**Environmental precautions:** Do not discharge into drains, surface waters, or ground water.

**Methods for cleanup:** Soak spilled material with inert absorbent materials. Transfer to a suitable container for disposal.

## 7. HANDLING AND STORAGE

### Handling

Keep containers tightly closed. Vapors are heavier than air and spread along the ground. Use only in adequately ventilated areas. Keep away from heat and sources of ignition! Do not eat or drink in the work area. Practice good hygiene.

# Safety Data Sheet



**RCC Corrosion Control / SDS #: RCC-20381 / Revision Date: 09/01/2022**

---

## Storage

Store in original closed containers away from heat and sources of ignition. Avoid storage in areas where the temperature exceeds 122 °F (50 °C). Keep away from food, drink, and animal foodstuffs.

Incompatible with Oxidizing agents, Metal halogenides, and Peroxides. .

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### EXPOSURE LIMITS :

Component	CAS#	Reference	Exposure Limits
Styrene	100 42-5	ACGIH OSHA NIOSH	20 ppm, TWA/40 ppm STEL 100 ppm/200 ppm ceiling 50 ppm/100 ppm ceiling

### Exposure Controls

#### Occupational exposure controls

Ensure adequate ventilation, especially in confined areas. Consider all potential hazards of this material, applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting PPE.

#### Protective and hygiene measures

Do not inhale vapors. Wash hands before breaks and immediately after handling product. When using, do not eat, drink, or smoke. Treat subsequently with skin cream. Remove and wash contaminated clothing before re-use.

#### Respiratory protection

If local ventilation is insufficient, wear suitable NIOSH-approved breathing apparatus or respirator.

#### Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl, or neoprene, with a minimum thickness of 0.028 inch (0.7 mm), permeation time of approximately 480 minutes (8 hrs.). Requirements may vary as a function of use. Therefore, it is necessary to adhere to the recommendations of the protective glove manufacturer.

#### Eye protection

Tight fitting goggles are recommended. Have a suitable eye wash station or bottle nearby in case of splashing product into eye(s).

#### Skin protection

Wear long-sleeved clothing. A solvent-resistant apron is recommended.

# Safety Data Sheet



RCC Corrosion Control / SDS #: RCC-20381 / Revision Date: 09/01/2022

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Liquid

**Odor:** Pungent

**Odor Threshold:** 0.1 ppm

**pH:** No data available

**Melting/freezing point:** -24°F (-31°C)

**Boiling point:** 293°F (145°C)

**Boiling range:** No data available

**Flash point (Tag closed cup):** 79°F (26.1°C)

**Evaporation rate:** < 1 Ethyl Ether

**Flammability: Lower Limit:** 1.1% (V) **Upper Limit:** 6.1% (V)

**Vapor pressure:** 0.851 kPa @ 77°F (25°C)

**Vapor density:** 3.6 (Air = 1)

**Relative density:** 1.056 g/cm<sup>3</sup> (8.81 lb/gal) @ 68°F (20°C)

**Solubility in water:** Insoluble

**Partition coefficient (n-octanol/water):** No data available

**Auto-ignition temperature:** No data available

**Decomposition temperature:** No data available

**Viscosity (dynamic):** No data available

## 10. STABILITY AND REACTIVITY

**Reactivity:** No decomposition of stored and applied as directed.

**Chemical stability:** Stable under normal conditions.

**Conditions to avoid:** Avoid heat and ignition sources.

**Materials to avoid:** Oxidizing agents, Metal halides, Peroxides

**Hazardous decomposition products:** Carbon dioxide, carbon monoxide, as well as flammable, corrosive/irritant, and toxic gases.

# Safety Data Sheet



**RCC Corrosion Control / SDS #: RCC-20381 / Revision Date: 09/01/2022**

---

## **11. TOXICOLOGICAL INFORMATION**

**Primary routes of exposure:** Inhalation, Skin contact, Eye contact. Ingestion is possible, but not likely under normal conditions.

**Symptoms related to physical, chemical and toxicological characteristics:**

Harmful by inhalation. Inhalation of high vapor concentrations may result in headache, dizziness, drowsiness, nausea, and vomiting.

Causes skin and eye irritation and dermatitis.

**Styrene**

**CAS # 100-42-5**

Acute Oral Toxicity	LD <sub>50</sub> Rat: 2650 mg/kg
Acute Dermal Toxicity	LD <sub>50</sub> Rabbit >2000 mg/kg
Acute Inhalation Toxicity	LC <sub>50</sub> Rat: 12 mg/l , 4h

## **12. ECOLOGICAL INFORMATION**

Avoid contamination of ground water or waterways. Do not discharge into sewers.

Product is not readily biodegradable. Toxic to aquatic organisms.

May cause long term adverse effects in the aquatic environment.

## **13. DISPOSAL CONSIDERATIONS**

Dispose of in accordance with Federal, State or Local regulations.

Contaminated packaging should be emptied as far as possible before disposal.

## **14. TRANSPORT INFORMATION**

**DOT SHIPPING CLASSIFICATION:**

UN NUMBER: UN1866

PROPER SHIPPING NAME: Resin Solution, flammable

TRANSPORTATION HAZARD CLASS: 3

PACKING GROUP: II

HAZARD LABEL: 3

# Safety Data Sheet



**RCC Corrosion Control / SDS #: RCC-20381 / Revision Date: 09/01/2022**

---

## **IMDG (Marine) SHIPPING CLASSIFICATION:**

IMDG CODE: 3

UN NUMBER: UN1866

MARINE POLLUTANT: No

EmS: F-E; S-E

IMDG PACKING GROUP: III

HAZARD LABEL: 3

### **Description of the goods**

RESIN SOLUTION

### **Other applicable information (marine transport)**

Viscous substance – excepted quantity if in containers with a capacity up to 30 l (subsection 2.3.2.5 IMDG Code)

## **IATA (Air) SHIPPING CLASSIFICATION:**

ICAO/IATA-DGR: 3

UN NUMBER: UN1866

HAZARD LABEL: 3

IATA-packing instructions – Passenger: 309

IATA-max. quantity – Passenger: 60L

IATA – packing instructions – Cargo: 310

IATA –max. quantity – Cargo: 220L

IAO packing group: III

Limited quantity Passenger: Y309 / 10 L

### **Description of the goods**

RESIN SOLUTION

## **15. REGULATORY INFORMATION**

All components of this product conform to the following national inventory requirements. US TSCA, EU EINECS and Canada DSL

### **SARA Title III**

The following ingredients are subject to the supplier notification requirements of Section 313 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part 37

Styrene (1,000 Lbs. RQ)



# Safety Data Sheet



**RCC Corrosion Control / SDS #: RCC-20381 / Revision Date: 09/01/2022**

---

## OTHER FEDERAL REGULATIONS

Components of this product are subject to RCRA Hazardous Waste requirements, Clean Air Act (CAA) Hazardous Air Pollutants requirements and OSHA Process Safety Management (PSM) high hazard requirements.

## CANADIAN REGULATIONS

Same as OSHA GHS Classification

## STATE REGULATIONS

### California Proposition 65

**WARNING:** This product contains styrene, a chemical known to the state of California to cause cancer.

The components of this product may be included on the various state hazardous materials lists noted below.

California Hazardous Substances List/Permissible Exposure List  
California Toxic air contaminants  
Connecticut Permissible Exposure Limits  
Delaware List of Chemicals and RQs  
Hawaii Permissible Exposure Limits  
Idaho Toxic Air Pollutants  
Illinois Toxic Air Contaminants List  
Louisiana Toxic Air Pollutants  
Maine Hazardous Air Pollutants  
Maryland Toxic Air Pollutants for Existing Sources  
Massachusetts Hazardous Substances List  
Michigan Permissible Exposure Limits  
Minnesota Hazardous Substances  
Minnesota Permissible Exposure Limits  
Nebraska Hazardous Air Pollutants  
New Jersey RTK Hazardous Substances List/TCPA Extremely Hazardous Substances List  
New York List of Hazardous Substances  
Ohio Toxic Air Contaminants  
Oklahoma Toxic Air Contaminants  
North Carolina TAP Emissions Rates Requiring a Permit  
Pennsylvania Hazardous Substances List  
Rhode Island Toxic Air Contaminants  
Tennessee Permissible Exposure Limits  
Vermont Hazardous Air Contaminants/Permissible Exposure Limits  
Washington Permissible Exposure Limits for Airborne Contaminants.  
West Virginia Toxic Air Pollutant List  
Wisconsin hazardous Air Contaminants

# Safety Data Sheet



**RCC Corrosion Control / SDS #: RCC-20381 / Revision Date: 09/01/2022**

---

**Note:** Entries under Section 15 are not intended to be all inclusive of Federal and State laws and regulations. Please consult the appropriate agencies for further clarification of any requirements.

## **16. OTHER INFORMATION**

**Disclaimer:** The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text